

Nano Breathing Air B1-Series NBM 720

- * Free standing absorber
- * Floor or wall mounted
- * Requires no power
- * Easy to replace catalyst purifier cartridges
- * 2 years warranty



Operating pressure	bar	Max 12	
Recommended operating temperature	Celcius	1.5 - 30	
Inlet quality requirements ²⁾	Particulate size	0.5 micron	
	Min pressure dew point	-40° C pdp	
	Max oil content	0.05 mg/m3	
Outlet rated flow ¹⁾	Nm3/hour	1.200	
Inlet & Outlet connection	NPT (f)	2"	
Dimensions HxWxD	MM	400 x 742 x 870	
Weight	Kg	142	

- service guidelines*
- M1 and M01 coalescing filter elements should be changed every year
 - AC elements should be changed every 1000 hours, or 6 months, whichever is sooner
 - purification cartridges have an estimated life of 12000 hours, or 2 years, whichever is sooner ⁽³⁾
 - control valves should be changed every 4 years
 - refer to user guide for full service details

- ¹⁾ At inlet conditions of 7 barg and 35° C and 35° C ambient temperature.
For all other operating conditions please contact our Sales Department.
- ²⁾ If the air does not meet these conditions please contact our Sales Department to confirm the additional treatment required.