

Nano Desiccant D2-Series Air Dryer NDL 110

- * Everything needed for installation in the box
- * Moisture & particulate protection of production process
- * Lower life cycle costs
- * Including energy saving outlet dew point control & display ¹⁾
- * Model can be easily wall mounted
- * Safe and quiet operation
- * 2 years warranty



Voltage	V	100 to 240v AC	Optional: 24V ¹⁾
Frequency	Hz	50 or 60hz	
Power rating	W	35	
Operating pressure	bar	Min 4 – Max 16	
Recommended operating temperature	Celcius	1.5 - 35	
Max water content	ISO Class	2 (-40 C pdp)	Optional: 1 (-70 C)
Inlet & Outlet	BSPP	1"	
Rated flow @ 7 bar	Sfcm	106	
	Nm3/hour	180.0	
Dimensions HxWxD	MM	1245 x 432 x 330	
Weight	Kg	78.0	

pressure correction factors ⁵⁾

inlet air pressure (barg)	4	5	6	7	8	9	10	11	12	13	14	16
correction factor	0.63	0.75	0.88	1.00	1.13	1.25	1.38	1.50	1.63	1.75	1.88	2.13

temperature & dew point correction factors ⁵⁾

inlet air temperature (°C)	25	35	40	45	50	pressure dew point (°C)	-20	-40	-70
correction factor	1.00	1.00	0.97	0.88	0.73	correction factor	1.10	1.00	0.70

- service guidelines*
- desiccant cartridges should be changed every 2 years
 - valves should be changed every 4 years
 - dew point meters should be serviced every 2 years (optional)
 - refer to user guide for full service details

¹⁾ Also deliverable without dew point control & display (contact our Sales Department)

⁵⁾ Rough guideline only